

**Mission Success** Ensign-Bickford Aerospace & Defense Company (EBAD) is dedicated to supporting our customers in the aerospace and defense industry through on-time delivery of innovative products that exceed expectations and assure mission success.

# TiNi<sup>™</sup> Pin Puller

EBAD's TiNi<sup>™</sup> Pin Pullers are utilized in satellite applications to provide a simple and effective non-pyro separation system between two components where a pull force is required. Ranging in size from a 5 lbf (22 N) to 1,000 lbf (4,450 N) pull force, the pin pullers offer a versatile solution from small satellite solar array deployments, launch locks for optical payloads and antenna releases.

Easy to use, resting the device is straightforward with our custom reset tools and requiring no parts to replace.

## **Principle of Operation**

The pin puller is a reliable fast operating device that ultilzes a Shape Memory Alloy (SMA) wire to release a latch to allow for the internal compression springs to retract the pin.

In the fully reset mode, the internal circuit is closed. When sufficient power is applied, the current raises the temperature of the SMA wire and subsequently contracts at its transition temperature. This allows internal ball locks to release and internal drive springs to retract the pin into the body of the device. Once retracted, the circuit is open allowing no power to continue to heat the SMA wire and provides the user with positive feedback that the device has actuated.

The device is reset with a custom tool that either pulls the pin out from the front or pushes it out from the rear.

## Construction

Utilizing a Shape Memory Alloy (SMA) wire, the wire is threaded through a latch and attached to the electrical contacts. The latch retains an internal ball bearings that keeps the compressed drive springs in place before actuation. Another smaller internal reset spring is installed to assist in the reset process.

The pin puller is fully vented and typically the enclosure is made with aluminum alloy with a titanium flange. The output pin is made with stainless steel with a tiolon finish.

Alternative voltages utilize an internal resistor to protect the SMA wire from overheating.

# **Applications**

Since 1996 Mars Global Surveyor mission, EBAD's TiNi<sup>™</sup> Pin Pullers have extensive heritage in space applications. Such applications include solar array and instrument deployment, instrument launch locks, optic cover releases, and other space applications where a pull force is needed. In addition, the pin pullers have high non-actuated side load capability that can withstand rigourous launch vehicle environmental levels.

No .: P25-1664

## **Key Features**

- Non-pyrotechnic
- Easy to field reset and simple to use
- Minimum 50 cvcles
- · Redundant firing circuit
- Maximum reliability thru design simplicity
- Flight pedigree and testability

Alternative applications include missile fin locks and underwater acutations with our subsea versions.



TiNi<sup>™</sup> Pin Puller Launch lock example (before actuation)



### **TiNi<sup>™</sup> Pin Puller Family Technical Specifications**

Pin Puller Family	NANO P5	P5	P10	P25	P50	P100	P1000
Pull Force	5 lbf (22 N)		10 lbf (44 N)	25 lbf (111 N)	50 lbf (222 N)	100 lbf (445 N)	1,000 lbf (4,450 N)
Side Load (actuation)	7 lbf (31.1 N)	10 lbf (44.5 N)	20 lbf (89 N)	50 lbf (222 N)	100 lbf (445 N)	200 lbf (890 N)	500 lbf (2,224 N)
Side Load (non-actuation)	20 lbf (8.9 N)	100 lbf (444.8 N)	330 lbf (1,468 N)	400 lbf (1,823 N)	490 lbf (2,180 N)	600 lbf (2,670 N)	Contact EBAD
Mass	.73 oz (18 g)	1.06 oz (30 g)	1.7 oz (48 g)	2.6 oz (75 g)	5.3 oz (150 g)	12.7 oz (360 g)	17 oz (482 g)
Operating Current	.5 to 2 A	.4 to 1.5 A	.6 to 2 A	1.25 A to 4.5 A	2.25 A to 6.5 A	2.25 A to 6.5 A	2.75 A to 8.75 A
Resistance	5.2±.5 Ω	7.7±.5 Ω	5.8±.5 Ω	3.1±.3 Ω	2.7±.3 Ω	3.1±.3 Ω	2.2±.3 Ω
Function Time @ 23°C	130 ms max @ .5 A		100 ms max @ 1 A	130 ms max @ 2 A	100 ms max @ 4 A	100 ms max @ 4 A	75 ms max @ 4 A
Cycle Life (min)	100				100	100	50
Operating Temp	-65°C + 70°C				-65°C + 70°C	-65°C + 70°C	-60°C + 70°C
Height (before pin retraction) <sup>x</sup>	1.25 in	1.625 in	1.72 in	2.54 in	3.50 in	4.255 in	4.605 in
Height (after pin retraction) <sup>Y</sup>	1.00 in	1.375 in	2 in	2.16 in	3.00 in	3.635 in	3.88 in
Max diameter (with flange) <sup>z</sup>	1.25 in	1.25 in	1.6 in	1.8 in	2.00 in	2.55 in	2.44 in x 2.44 in
Front/Rear Resettable	Yes Yes Yes Front Std; Rear Optional with growth in device					Contact EBAD	

Contact EBAD about alternative voltages/resistance and pin type

### TiNi<sup>™</sup> Pin Puller Mechanical Interface Drawing (for reference)



#### **ENSIGN-BICKFORD AEROSPACE & DEFENSE COMPANY** 640 HOPMEADOW STREET, P.O. BOX 429, SIMSBURY, CT 06070, USA www.EBAD.com

Attention: The information and recommendations described in this brochure cannot possibly cover every application of the products or variation of conditions under which the products are used. The recommendations here in are based on the manufacture's experience, research and testing. They are believed to be accurate, but no warranties are made, express or implied, in addition, the specifications contained herein are all nominal which represent our current products described may be subject to change. Please feel free to contact Ensign-Bickford Aerospace & Defense Company for verification. No Warranties or Liabilities: THE PRODUCTS DESCRIBED HEREIN are sold "AS IS" and without any warranty or guaranty, express, or implied, arising by law or otherwise including without limitation any warranty of merchantability or fitness for a particular purpose. Buyer and user agree further to release and discharge seller from any and all liabilities withouts or use of any product described herein whether or not such liability is occasioned by seller's negligence or based upon strict products liability or upon principles of indemnity or contribution. Content@2021 Ensign-Bickford Aerospace & Defense Company, Simsbury, CT 06070, U.S.A.

Cleared for Open Publication by the Defense Office of Prepublication and Security Review, Department of Defense 03/18/2022 22-S-1402

# www.EBAD.com

TiNi<sup>™</sup> Pin Puller

# TiNi<sup>™</sup> Pin Puller